# Xerox® VersaLink® C 7020/ 7025 / 7030 / 7000 - Europe
# Paper and Specialty Media Guide - June 2017

For your convenience, this guide includes the Recommended Media List.

**The Recommended Media List** contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance.

Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List for a specific Xerox® printer or digital press will give optimum performance. This is how Antalis can offer 100% Performance Guaranteed.

Important Notes:

All media is listed by product, paper type, paper tray settings - image quality, weight (standard gsm), re-order number, size, tray runability, and integrated office finisher runability.  The additional information column is for hints and tips on how to run certain media applications.

Machine reliability specifications may be affected by increased usage of Cardstock, Heavyweight Cardstock, Light Glossy Cardstock, Glossy Cardstock and Heavy Glossy Cardstock modes.  In addition, variances in machine reliability may occur due to extended use of some media types. Your Xerox service representative can advise you on using Cardstock, Heavyweight Cardstock, Light Glossy Cardstock, Glossy Cardstock and Heavy Glossy Cardstock  modes or special application media types for long duration copy/print runs.

Environmental Conditions may require that Glossy papers be fed one sheet at a time through Bypass.  Relative Humidity greater than 40% could cause multifeeds. Output may require removal at 25 sheets in the tray when not using a finisher.

The Integrated Office "A" Finisher is capable of stapling at maximum; (maximum number will decrease if paper weight is greater than 24lb / 90 gsm):
   50 Sheets of Letter (8.5 x 11" / A4), Executive (7.25 x 10.5), in Long Edge Feed (LEF);  or of Letter in Short Edge Feed (SEF)
   30 Sheets of Tabloid/Ledger (11 x 17" / A3),  Legal (8.5 x 14"), or 8.5 x 13"

The Office Finisher LX  is capable of stapling at maximum; (maximum number will decrease if paper weight is greater than 24lb / 90 gsm):
   50 Sheets of Paper up to the size of 11 x 17" / A3 Short Edge Feed (SEF)

100% Performance Guaranteed

Learn more at www.performance-guaranteed.com

# Xerox® Versalink® C7020/7025/7030 and VersaLink® C7000 - Recommended Media List - Europe - March 2017

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance.
Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List
for a specific Xerox® printer or digital press will give optimum performance.
This is how Antalis can offer 100% Performance Guaranteed.

**Trays 1,2,3, TTM, Bypass & HCF**

Plain / Bond / Recycled (60 - 105 gsm)
Light Glossy Cardstock (106 - 169 gsm)
Lightweight Cardstock (106 - 169 gsm)
Glossy Cardstock (170 - 216 gsm)
Cardstock (170 - 256 gsm)
Heavy Glossy Cardstock (217 - 256 gsm)
Heavyweight Cardstock (217 - 356 gsm)
Envelope
Labels

**Paper Types are selected when Paper Tray is closed**

**VersaLink®**
**C 7020/ 7025 / 7030 / 7000**
**RML**
**Europe**
**V 1.0 - June 2017**

**Simplex / Duplex Capabilities**
A = Auto Duplex
S = Simplex Only
M = Manual Duplex    n = not supported

**Finisher Capabilities**
· Capable of Stacking Paper Type
t Capable of Stapling Paper Type
n = not supported

| Media | Paper Type Setting | Weight | Re-Order # | Type | Size | IOT 1 | STM/1TM/3TM 2 | STM/1TM/3TM 3 | STM/1TM/3TM 4 | TTM 2 | TTM 3 | TTM 4 | Bypass 5 | HCF 6 | Integrated (A) Office Finisher Stack | Integrated (A) Office Finisher Staple | Office (SB) Finisher LX Stack | Office (SB) Finisher LX Staple | Additional Information |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Xerox® Business | Plain | 80 gsm | 3R91820 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R91821 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| Xerox® Recycled | Plain | 80 gsm | 3R91165 | Recycled | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R91166 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| Xerox® Recycled Supreme 100% | Plain | 80 gsm | 3R95860 | Recycled | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R95861 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| Xerox® Premier | Plain | 80 gsm | 3R91720 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R91721 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Bond | 90 gsm | 3R91854 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R91853 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| Xerox® Exclusive | Plain | 80 gsm | 3R90208 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R91712 | 4 hole | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R90209 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Bond | 90 gsm | 3R90600 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R90618 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| Xerox® Digital Colour Impressions | Plain | 80 gsm | 3R97661 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R97662 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Bond | 90 gsm | 3R97663 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R97664 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Bond | 100 gsm | 3R97666 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R97667 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Lightweight Cardstock | 120 gsm | 3R98685 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R97669 | | A3 | n | A | A | A | A | n | n | A | n | · | t | · | t | |
| | | 160 gsm | 3R98007 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | | | 3R98008 | | A3 | n | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Heavyweight Cardstock | 250 gsm | 3R97671 | | A3 | S | S | S | S | S | n | n | n | n | n | n | n | n | |
| | | | 3R98687 | | A4 | S | S | S | S | S | S | S | n | n | n | n | n | n | |

# Xerox® Versalink® C7020/7025/7030 and VersaLink® C7000 - Recommended Media List - Europe - March 2017

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance.
Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List
for a specific Xerox® printer or digital press will give optimum performance.
This is how Antalis can offer 100% Performance Guaranteed.

**Trays 1,2,3, TTM, Bypass & HCF**

| Colour | Paper Type |
|---|---|
| (light blue) | Plain / Bond / Recycled (60 - 105 gsm) |
| (yellow) | Light Glossy Cardstock (106 - 169 gsm) |
| (orange) | Lightweight Cardstock (106 - 169 gsm) |
| (purple) | Glossy Cardstock (170 - 216 gsm) |
| (pink) | Cardstock (170 - 256 gsm) |
| (blue) | Heavy Glossy Cardstock (217 - 256 gsm) |
| (magenta) | Heavyweight Cardstock ( 217 - 356 gsm) |
| (green) | Envelope |
| (grey) | Labels |

**Paper Types are selected when Paper Tray is closed**

**Simplex / Duplex Capabilities**
A = Auto Duplex
S = Simplex Only
M = Manual Duplex    n = not supported

**Finisher Capabilities**
· Capable of Stacking Paper Type
t Capable of Stapling Paper Type
n = not supported

**VersaLink®**
C 7020/ 7025 / 7030 / 7000
RML
Europe
V 1.0 - June 2017

| Media | Paper Type Setting | Weight | Re-Order # | Type | Size | IOT 1 | STM/1TM/3TM 2 | STM/1TM/3TM 3 | STM/1TM/3TM 4 | TTM 2 | TTM 3 | TTM 4 | Bypass 5 | HCF 6 | Integrated (A) Office Finisher Stack | Integrated (A) Office Finisher Staple | Office (SB) Finisher LX Stack | Office (SB) Finisher LX Staple | Additional Information |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Xerox® Digital Colour Colotech+ | Bond | 90 gsm | 3R94641 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | Bond | 90 gsm | 3R94642 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Bond | 100 gsm | 3R94646 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | Bond | 100 gsm | 3R94647 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Lightweight Cardstock | 120 gsm | 3R94651 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | Lightweight Cardstock | 120 gsm | 3R94652 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Lightweight Cardstock | 160 gsm | 3R94656 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | Lightweight Cardstock | 160 gsm | 3R94657 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Cardstock | 200 gsm | 3R94661 | | A4 | A | A | A | A | A | A | A | M | A | · | t | · | t | |
| | Cardstock | 200 gsm | 3R94662 | | A3 | A | A | A | A | A | n | n | M | n | · | t | · | t | |
| | Heavyweight Cardstock | 220 gsm | 3R94668 | | A4 | S | S | S | S | S | S | S | n | n | | t | n | n | |
| | Heavyweight Cardstock | 220 gsm | 3R94669 | | A3 | S | S | S | S | S | n | n | n | n | | t | n | n | |
| | Heavyweight Cardstock | 250 gsm | 3R94671 | | A4 | S | S | S | S | S | S | S | n | n | n | n | n | n | |
| | Heavyweight Cardstock | 250 gsm | 3R94672 | | A3 | S | S | S | S | S | n | n | n | n | n | n | n | n | |
| Xerox® Digital Colour Colotech+ GOLD | Bond | 90 gsm | 3R98837 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | Bond | 90 gsm | 3R98839 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Bond | 100 gsm | 3R98842 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | Bond | 100 gsm | 3R98844 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Lightweight Cardstock | 120 gsm | 3R98847 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | Lightweight Cardstock | 120 gsm | 3R98848 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Lightweight Cardstock | 160 gsm | 3R98852 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | Lightweight Cardstock | 160 gsm | 3R98854 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Cardstock | 200 gsm | 3R97967 | | A4 | S | S | S | S | S | S | S | M | S | · | t | · | t | |
| | Cardstock | 200 gsm | 3R97968 | | A3 | S | S | S | S | S | n | n | M | n | · | t | · | t | |
| | Heavyweight Cardstock | 220 gsm | 3R97971 | | A4 | S | S | S | S | S | S | S | n | n | | t | n | n | |
| | Heavyweight Cardstock | 220 gsm | 3R97972 | | A3 | S | S | S | S | S | n | n | n | n | | t | n | n | |
| | Heavyweight Cardstock | 250 gsm | 3R98975 | | A4 | S | S | S | S | S | S | S | n | n | n | n | n | n | |
| | Heavyweight Cardstock | 250 gsm | 3R98976 | | A3 | S | S | S | S | S | n | n | n | n | n | n | n | n | |
| Xerox® Colotech+ Natural White | Bond | 100 gsm | 3R97102 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | Bond | 100 gsm | 3R97103 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Lightweight Cardstock | 160 gsm | 3R95956 | | A4 | A | A | A | A | A | A | A | A | A | · | t | · | t | |
| | Lightweight Cardstock | 160 gsm | 3R95957 | | A3 | A | A | A | A | A | n | n | A | n | · | t | · | t | |
| | Cardstock | 200 gsm | 3R95958 | | A4 | S | S | S | S | S | S | S | M | S | · | t | · | t | |
| | Cardstock | 200 gsm | 3R95959 | | A3 | S | S | S | S | S | n | n | M | n | · | t | · | t | |

# Xerox® Versalink® C7020/7025/7030 and VersaLink® C7000 - Recommended Media List - Europe - March 2017

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance.
Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List
for a specific Xerox® printer or digital press will give optimum performance.
This is how Antalis can offer 100% Performance Guaranteed.

**Trays 1,2,3, TTM, Bypass & HCF**

- Plain / Bond / Recycled (60 - 105 gsm)
- Light Glossy Cardstock (106 - 169 gsm)
- Glossy Cardstock (170 - 216 gsm)
- Heavy Glossy Cardstock (217 - 256 gsm)
- Envelope
- Lightweight Cardstock (106 - 169 gsm)
- Cardstock (170 - 256 gsm)
- Heavyweight Cardstock ( 217 - 356 gsm)
- Labels

**Paper Types are selected when Paper Tray is closed**

**Simplex / Duplex Capabilities**
A = Auto Duplex
S = Simplex Only
M = Manual Duplex    n = not supported

**Finisher Capabilities**
· Capable of Stacking Paper Type
t Capable of Stapling Paper Type
n = not supported

**VersaLink®**
**C 7020/ 7025 / 7030 / 7000**
**RML**
**Europe**
**V 1.0 - June 2017**

| Media | Paper Type Setting | Weight | Re-Order # | Type | Size | IOT 1 | STM/1TM/3TM 2 | 3 | 4 | TTM 2 | 3 | 4 | Bypass 5 | HCF 6 | Integrated (A) Office Finisher Stack | Staple | Office (SB) Finisher LX Stack | Staple | Additional Information |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Xerox® Colour Laser Matt CD labels | Lightweight Cardstock | | 3R97514 | 2 up | A4 | S | n | n | n | n | n | n | S | S | · | n | n | n | Environmental conditions may require that this product be fed one sheet at a time. (*1) If misfeed still occurs when feeding one sheet at a time, load paper curled upward. |
| Xerox® Digital Colour Colotech+ Gloss Coated | Light Glossy Cardstock | 120 gsm | 3R90336 | Gloss Text | A4 | A | A | A | A | A | A | A | A | A | · | n | · | t | Bypass inhibited due to excessive jams. Loading from Trays 1-4 recommended. Environmental conditions may require that this product be fed one sheet at a time. (*1) (If misfeed still occurs when feeding one sheet at a time, load paper curled upward. ) |
| | | | 3R90337 | | A3 | A | A | A | A | A | n | n | A | n | · | n | · | t | |
| | Light Glossy Cardstock | 140 gsm | 3R90339 | Gloss Text | A4 | A | A | A | A | A | A | A | A | A | · | n | · | t | |
| | | | 3R90340 | | A3 | A | A | A | A | A | n | n | A | n | · | n | · | t | |
| | Glossy Cardstock | 170 gsm | 3R90342 | Gloss Cover | A4 | S | S | S | S | S | S | S | M | S | · | n | · | t | |
| | | | 3R90343 | | A3 | S | S | S | S | S | n | n | M | n | · | n | · | t | |
| | Glossy Cardstock | 210 gsm | 3R90345 | Gloss Cover | A4 | S | S | S | S | S | S | S | M | S | · | n | · | n | |
| | | | 3R90346 | | A3 | S | S | S | S | S | n | n | M | n | · | n | · | n | |
| | Heavy Glossy Cardstock | 250 gsm | 3R90348 | Gloss Cover | A4 | S | S | S | S | S | S | S | n | n | n | n | n | n | Environmental conditions may require that this product be fed one sheet at a time from Trays 1-4. (*1) (Bypass cannot be used for media heavier than 216gsm.) When job is printed in low temperature and low humidity environment, poor transfer of toner may be observed. If poor transfer is observed, change 2nd transfer voltage offset |
| | | | 3R90349 | | A3 | S | S | S | S | S | S | S | n | n | n | n | n | n | |
| Xerox® Digital Colour Colotech + Silk Coated | Light Glossy Cardstock | 120 gsm | 3R90355 | Silk Text | A4 | A | A | A | A | A | A | A | A | A | · | n | · | t | Environmental conditions may require that this product be fed one sheet at a time from Trays 1-4 or Bypass. (*1) |
| | | | 3R90356 | | A3 | A | A | A | A | A | n | n | A | n | · | n | · | t | |
| | Light Glossy Cardstock | 140 gsm | 3R90358 | Silk Text | A4 | A | A | A | A | A | A | A | A | A | · | n | · | t | |
| | | | 3R90359 | | A3 | A | A | A | A | A | n | n | A | n | · | n | · | t | |
| | Glossy Cardstock | 170 gsm | 3R90361 | Silk Cover | A4 | S | S | S | S | S | S | S | M | S | · | n | · | t | |
| | | | 3R90362 | | A3 | S | S | S | S | S | n | n | M | n | · | n | · | t | |
| | Glossy Cardstock | 210 gsm | 3R90364 | Silk Cover | A4 | S | S | S | S | S | S | S | M | S | · | n | · | n | |
| | | | 3R90365 | | A3 | S | S | S | S | S | n | n | M | n | · | n | · | n | |
| | Heavy Glossy Cardstock | 250 gsm | 3R90367 | Silk Cover | A4 | S | S | S | S | S | S | S | n | n | n | n | n | n | Environmental conditions may require that this product be fed one sheet at a time from Trays 1-4. (*1) (Bypass cannot be used for media heavier than 216gsm.) When job is printed in low temperature and low humidity environment, poor transfer of toner may be observed. If poor transfer is observed, change 2nd transfer voltage offset |
| | | | 3R90368 | | A3 | S | S | S | S | S | S | S | n | n | n | n | n | n | |

# Xerox® Versalink® C7020/7025/7030 and VersaLink® C7000 - Recommended Media List - Europe - March 2017

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance.
Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List
for a specific Xerox® printer or digital press will give optimum performance.
This is how Antalis can offer 100% Performance Guaranteed.

**Trays 1,2,3, TTM, Bypass & HCF**

- Plain / Bond / Recycled (60 - 105 gsm)
- Light Glossy Cardstock (106 - 169 gsm)
- Glossy Cardstock (170 - 216 gsm)
- Heavy Glossy Cardstock (217 - 256 gsm)
- Envelope
- Lightweight Cardstock (106 - 169 gsm)
- Cardstock (170 - 256 gsm)
- Heavyweight Cardstock (217 - 356 gsm)
- Labels

**Paper Types are selected when Paper Tray is closed**

**VersaLink®**
**C 7020/ 7025 / 7030 / 7000**
**RML**
**Europe**
**V 1.0 - June 2017**

**Simplex / Duplex Capabilities**
A = Auto Duplex
S = Simplex Only
M = Manual Duplex     n = not supported

**Finisher Capabilities**
·   Capable of Stacking Paper Type
t   Capable of Stapling Paper Type
n = not supported

| Media | Paper Type Setting | Weight | Re-Order # | Type | Size | IOT | STM/1TM/3TM | | | TTM | | | Bypass | HCF | Integrated (A) Office Finisher | | Office (SB) Finisher LX | | Additional Information |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | 1 | 2 | 3 | 4 | 2 | 3 | 4 | 5 | 6 | Stack | Staple | Stack | Staple | |
| Xerox® Colotech+ Supergloss (Coated 1 side) (*1) | Light Glossy Cardstock | 160 gsm | 3R97680 | | A4 | A | A | A | A | A | A | A | A | A | · | n | · | t | If jams occur when feeding from Tray 1-4 or HCF, switch to Bypass Tray for improved performance with Glossy papers. Environmental conditions (high humidity) may require that this product be fed 1 sheet at a time. |
| | | | 3R97681 | | A3 | A | A | A | A | A | A | A | A | n | · | n | · | t | |
| | Glossy Cardstock | 210 gsm | 3R97682 | | A4 | S | S | S | S | S | S | S | M | S | · | n | · | n | |
| | | | 3R97683 | | A3 | S | S | S | S | S | n | n | M | n | · | n | · | n | |
| | Heavy Glossy Cardstock | 250 gsm | 3R97686 | | A4 | S | S | S | S | S | S | S | n | n | n | n | n | n | Environmental conditions may require that this product be fed one sheet at a time from Trays 1-4. (*1) If misfeed still occurs when feeding one sheet at a time, load paper curled upward. (Bypass cannot be used for media heavier than 216gsm.) Jam may occur when high density originals printed to EXIT2 Tray. If the jam occured, use EXIT1 Tray. |
| | | | 3R97687 | | A3 | S | S | S | S | S | S | S | n | n | n | n | n | n | |
| Xerox® Colour Copier Laser Labels | Labels | | 3R93872 | 1 up | A4 | n | n | n | n | n | n | n | S | n | · | n | n | n | Labels once fed cannot be used. Bypass only. Excessive jams due to curl when fed from Trays 1-4. Low humidity environment (J/C zones) inhibited due to excessive media curl. Poor stacking at continuous running in A/C/J-zone. Removing the output one by one is recommended. |
| | | | 3R95813 | 4 up | A4 | n | n | n | n | n | n | n | S | n | · | n | n | n | |
| | | | 3R93874 | 8 up | A4 | n | n | n | n | n | n | n | S | n | · | n | n | n | |
| | | | 3R93875 | 14 up | A4 | n | n | n | n | n | n | n | S | n | · | n | n | n | |
| | | | 3R95815 | 21 up | A4 | n | n | n | n | n | n | n | S | n | · | n | n | n | |
| | | | 3R97524 | 24 up | A4 | n | n | n | n | n | n | n | S | n | · | n | n | n | |
| Xerox® High Speed Removable Labels | Labels | | 3R96177 | 16 up | A4 | S | S | S | S | S | S | S | S | S | · | n | n | n | Labels once fed cannot be used. Jams due to excessive curl may occur in A/C/J zones. Environmental conditions may require that this product be fed one sheet at a time from Bypass. (*1) |
| | | | 3R96178 | 24 up | A4 | S | S | S | S | S | S | S | S | S | · | n | n | n | |
| Xerox® Color Laser Dura Paper Label | Labels | | 3R97344 | 1 up | A4 | S | S | S | S | S | S | S | S | S | · | n | n | n | Labels once fed cannot be used. Smears may be observed in BW mode. <Workaround> (1) Print in color mode. (2) Increase the paper-to-paper pitch |
| Xerox® High Speed Laser Labels | Heavyweight Labels | | 3R96281 | 16 up | A4 | S | S | S | S | S | S | S | S | S | · | n | n | n | Labels once fed cannot be used. Smears may be observed in BW mode. <Workaround> (1) Print in color mode. (2) Increase the paper-to-paper pitch |
| Xerox® Supergloss Labels | Glossy Cardstock | | 3R97288 | 1 up | A4 | S | S | S | S | S | S | S | n | S | · | n | n | n | Bypass is inhibited due to excessive jams. Environmental conditions may require that this product be fed one sheet at a time. (*1) If misfeed still occurs when feeding one sheet at a time, load paper curled upward. A-zone is inhibited. Jam may occur when high density originals printed to EXIT2 Tray. If the jam occured, use EXIT1 Tray. Poor stacking at continuous running in A/C/J-zone. Removing the output one by one is recommended. |

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance.
Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List
for a specific Xerox® printer or digital press will give optimum performance.
This is how Antalis can offer 100% Performance Guaranteed.

**Trays 1,2,3, TTM, Bypass & HCF**

Plain / Bond / Recycled (60 - 105 gsm)
Light Glossy Cardstock (106 - 169 gsm)
Lightweight Cardstock (106 - 169 gsm)
Glossy Cardstock (170 - 216 gsm)
Cardstock (170 - 256 gsm)
Heavy Glossy Cardstock (217 - 256 gsm)
Heavyweight Cardstock ( 217 - 356 gsm)
Envelope
Labels

**Paper Types are selected when Paper Tray is closed**

**VersaLink®**

**C 7020/ 7025 / 7030 / 7000**

**RML**

**Europe**

**V 1.0 - June 2017**

**Simplex / Duplex Capabilities**

A = Auto Duplex

S = Simplex Only

M = Manual Duplex    n = not supported

**Finisher Capabilities**

· Capable of Stacking Paper Type

t Capable of Stapling Paper Type

n = not supported

| Media | Paper Type Setting | Weight | Re-Order # | Type | Size | IOT | STM/1TM/3TM | | | TTM | | | Bypass | HCF | Integrated (A) Office Finisher | | Office (SB) Finisher LX | | Additional Information |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | 1 | 2 | 3 | 4 | 2 | 3 | 4 | 5 | 6 | Stack | Staple | Stack | Staple | |
| Xerox® Colour Laser Gloss CD labels | Glossy Cardstock | | 3R97516 | 2 up | A4 | S | S | S | S | S | S | S | n | n | · | n | n | n | Bypass inhibited due to excessive jams. Loading from Trays 1-4 recommended. Environmental conditions may require that this product be fed one sheet at a time.  (*1) (If misfeed still occurs when feeding one sheet at a time, load paper curled upward.) |
| Envelopes | Envelope | 75 - 90 gsm | 7R96721 | Xerox® Digital C5 Envelope | 9 x 6.4 in | n | n | n | n | n | n | n | S | n | · | n | n | n | Misfeed jam may occur under high temperature/humidity condition or with envelopes with low stiffness. |
| | | | 7R96718 | Xerox® Digital DL Envelope | 8.7 x 4.3 in | n | n | n | n | n | n | n | S | n | · | n | n | n | |
| | | | 1144 | Riverseries DL Severn Self-Seal Envelope | 8.7 x 4.3 in | n | n | n | n | n | n | n | S | n | · | n | n | n | |
| | | | 1029 | Riverseries DL Severn Gummed Envelope | 8.7 x 4.3 in | n | n | n | n | n | n | n | S | n | · | n | n | n | |
| | | | 2234 | Riverseries C5 Congo Gummed Envelope | 8.7 x 4.3 in | n | n | n | n | n | n | n | S | n | · | n | n | n | |

(*1) "Environmental conditions" most typically refer to high humidity conditions such as A zone. Medium level humidity (B zone) also has some risk. In low humidity conditions (C or J zones), customers may be able to auto feed the media from trays, but if jams occur, fanning paper before loading is recommended. If jams still occur, feeding one sheet at a time is required.